

DP-330/330L

Fast and
ruggedized simplicity



HIGHLIGHTS AT A GLANCE:

- Easy-to-read control panel and simple drop-in paper loading
- Simple drop-in paper loading
- Fast printing
- Popular printer emulations provide compatibility
- DP-330 Receipt version / DP-330L Label version
- IP54 per IEC 529



DP-330/330L

With the Tally Dascom DP-330 series you can concentrate on your job and not on the printer. Although the printer is up to 10% smaller and 40% lighter than comparable models, it makes no compromises. A variety of interfaces and emulations allow the use of DP-330/DP-330L in different environments.

Whether water, dust or vibrations, this printer operates reliably. Whether in the basic variant DP-330 for receipt documents or in the label version as DP-330L. Thanks to different holders, the printer can easily install on mobile dollies or in vehicles.

TECHNICAL SPECIFICATIONS

Print speed	Up to 4 inch/sec (101,6 mm/sec)
Resolution	203 dpi (8 dots/mm)
Lifetime print head	50 km
Memory	36 MB FLASH, 32 MB DRAM
Print width	Up to 72 mm
Interfaces Standard	USB 2.0
Interfaces Optional	Bluetooth (4.0) or WiFi (802.11 b/g/n)
Bluetooth	Compatible Bluetooth 4.0 Stack Protocols: L2CAP, RFCOMM, SDP Profile: GAP, SDAP, SPP, BTLE
WiFi	Encryption: WEP, WPA-PSK/TKIP, WPA2-AES
Administration	Config Tool
Emulations	ESC/POS, ZPL II, CPCL
Roll diameter	Max. diameter 50,8 mm for DP-330 and 66 mm for DP-330L
Roll capacity	Approx. 28,6 m (equals 188 6" receipts) for DP-330 Approx. 52 m (equals 346 pcs. 6" labels) for DP-330L
Battery	Rechargeable 3 cells Lithium-Ion (3.000 mAh) Endurance more then 3.500 inchs per charge/8 hours shift without WiFi Charging time 3,5 hours
Weight	0,66 kg (incl. battery) for DP-330 0,69 kg (incl. battery) for DP-330L
Dimensions	117 x 155 x 69 mm (W x D x H) for DP-330 117 x 155 x 79 mm (W x D x H) for DP-330L
Voltage	12,6 V
Temperature	-10° to +45° C (printing); -25° to 65° C (storage)
Humidity	0% to 65% (printing); 0% to 98% (storage)
MTBF	10.000 hours
Drivers	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022; Android; iOS (only WiFi)
Certifications	CE, FCC Class B

Configurations:

- **DP-330** Receipt model
- **DP-330 BT** Receipt model with Bluetooth
- **DP-330 WiFi** Receipt model with WiFi
- **DP-330L** Label model
- **DP-330L BT** Label model with Bluetooth
- **DP-330L WiFi** Label model with WiFi

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047