

**Network
model**
with integrated
Ethernet interface

T5040

Robust, fast
and powerful



HIGHLIGHTS AT A GLANCE:

- Processing of diverse materials
- Automatic adjustment of print-head distance
- Automatic registration of forms, passports and passbooks
- Automatic paper edge detection
- Simultaneous connection to several systems via serial, parallel or USB and 2nd serial interface
- Unsurpassed processing time-typical passbook print in 2.2 seconds
- DIN letter printing in 11.8 seconds

T5040

With a speed up to 600 characters / sec. The T5040 processes a variety of print media, such as passports and passbooks, checks and receipts, through to A5 and A4 form sets. The flatbed design guarantees the safest paper handling, and additional features such as automatic document orientation and automatic print head spacing (AGA) provide unsurpassed ease of use.

The T5040 standard supports the printing of individual documents via the serial interface with a security protocol, as required in bank environments. By default, there is also a USB and parallel interface for flexible connections and for multi-user use. A model with a 2nd serial port is also available.

TECHNICAL DATA

Print Speed	Fastest Speed: 600 cps Character density 10 / 12 / 15 cpi <i>HS Draft</i> 400 / 480 / 600 cps <i>Draft</i> 300 / 360 / 400 cps <i>LQ</i> 133 / 160 / 200 cps
Resolution	up to 360 x 360 dpi
Character Density	10, 12, 15, 16.6, 17.1, 20 cpi
Line Density	1, 2, 3, 4, 6, 8 lpi
Print Head Lifetime	400 Million dots per pin
Memory	256 kB
Interfaces	Standard Version: Parallel (Bi-directional), Serial (RS-232) and USB 2.0 N Version: Ethernet (10/100 BaseT), Parallel (Bi-directional), Serial (RS-232) and USB 2.0 2x serial Version: Parallel (Bi-directional), 2x Serial (RS-232) and USB 2.0
Emulations	IBM 4722, IBM ProPrinter XL24e, Epson ESC P/2, Olivetti PR50/PR2/PRe
Fonts	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic OCR-A/B, 10 Barcodes
Consumables	Ribbon: 10million characters
Paper Handling	Manual single sheet insertion from front, automatic paper alignment, automatic paper edge detection (left)
Copies	1 original + 4copies
Paper Types	Single sheet, multi-part forms, passbooks and passports up to 2,0 mm thickness
Paper Weight	60-260 g/m ²
Paper Format	Width: 70 to 240 mm; Length: 70 to 500 mm (Paper) Width: 105 to 235 mm; Length: 125 to 210 mm (Passbook/Passport opened)
Weight	9,8 kg
Dimension	378 x 280 x 168 mm (W x D x H)
Noise	55 dB(A)
Power Voltage	230 V - 50/60 Hz
Power Consumption	9 W (Stand-By); 73 W (Printing)
Temperature	+5° to +40° C; 10% to 85% rel. humidity
Print Volume	5.000 transactions per month
MTBF	10.000 hours
Driver	Windows 8/8.1/10/11 and Server 2012/2016/2019/2022

Configurations:

- **T5040** Standard model
- **T5040 MSR-H** Model with horizontal magnetic stripe reader
- **T5040N** Model with integrated Ethernet

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047