

**2600+**  
High performance  
at low cost



**HIGHLIGHTS AT A GLANCE:**

- Print speed up to 683 cps
- Up to 20.000 pages/month
- 80 columns / A4
- 24 wires print head for excellent print quality
- Straight paper path for easy paper handling
- Metal tear bar
- Ethernet with IPv6 support, parallel and USB interface as standard
- USB Host interface for easy firmware-update
- User-friendly, backlit illuminated LC display

# 2600+

The new Tally Dascom 2600+ is the **further developed variant** of the successful Tally Dascom 2600.

Thanks to the two-part upper cover, the printed pages can now be removed even more easily from the end of the book. A **metal tear bar** ensures that even thicker paper or multiple sets are separated cleanly. The **durable ribbon for 10 million characters** can easily be replaced. The new ribbon mask ensures that the ribbon is inserted correctly. In addition to the standard interfaces **USB, Parallel and Ethernet** (with IPv6 support), the Tally Dascom 2600+ now also has a **USB host interface**, so that new firmware can easily be installed with the help of a USB stick.

The new print head is not only **up to 20% faster**, but also allows for a **noise reduction of up to 2 decibels** thanks to its design.

## TECHNICAL DATA

|                                |                                                                                                                                                                                                            |
|--------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Print speed</b>             | Fastest Speed: 683 cps<br>Character density 10 / 12 / 15 cpi<br><i>HS Draft</i> 600 / 683 / 683 cps<br><i>Draft</i> 513 / 513 / 513 cps<br><i>NLQ</i> 228 / 273 / 171 cps<br><i>LQ</i> 114 / 137 / 171 cps |
| <b>Resolution</b>              | Up to 360 x 360 dpi                                                                                                                                                                                        |
| <b>Throughput</b> (ECMA 132)   | 457 pages per hour                                                                                                                                                                                         |
| <b>Character density</b>       | 10, 12, 15, 17.1, 20 cpi                                                                                                                                                                                   |
| <b>Line density</b>            | 2, 3, 4, 6, 8, 12 lpi                                                                                                                                                                                      |
| <b>Printhead lifetime</b>      | 500 Mio. impact per wire                                                                                                                                                                                   |
| <b>RAM</b>                     | 256 kB                                                                                                                                                                                                     |
| <b>Interface Standard</b>      | Parallel (Bi-directional), USB 2.0 and Ethernet (10/100BaseT, IPv6)<br>USB Host                                                                                                                            |
| <b>Interface Optional</b>      | Serial RS-232                                                                                                                                                                                              |
| <b>Administration</b>          | Tally WebPanel via Ethernet; Config-Tool via USB/Parallel                                                                                                                                                  |
| <b>Emulations Standard</b>     | IBM ProPrinter XL24, Epson ESC P/2, MTPL + Barcode + LCP<br>Epson FX 9-Nadel Emulation<br><b>LA Upgrade Kit:</b> DEC PPL2                                                                                  |
| <b>Fonts</b>                   | HS Draft, Draft, Courier, Roman, Sans Serif, Prestige, Script, OCR-A/B, 14 Barcodes and large character printing                                                                                           |
| <b>Consumables</b>             | Ribbon: 10 Mio. characters                                                                                                                                                                                 |
| <b>Paper handling Standard</b> | One tractor usable as push (front or rear) or pull (top) version, continuous paper with straight paper path and park position, cut sheet front insertion, tear or front off                                |
| <b>Paper handling Optional</b> | Additional push tractor (rear)                                                                                                                                                                             |
| <b>Copies</b>                  | Push tractor front: 1 original + 5 copies;<br>Pull tractor top: 1 original + 5 copies;<br>Cut sheet: 1 original + 5 copies                                                                                 |
| <b>Paper types</b>             | Cut sheets, continuous forms, multi-part forms                                                                                                                                                             |
| <b>Paper weight</b>            | 60-120 g/m <sup>2</sup>                                                                                                                                                                                    |
| <b>Paper format</b>            | Width: 76 to 278 mm; Length: 76 to 599 mm                                                                                                                                                                  |
| <b>Weight</b>                  | 8,1 kg                                                                                                                                                                                                     |
| <b>Dimensions</b>              | 458 x 265 x 200 mm (W x D x H)                                                                                                                                                                             |
| <b>Noise</b>                   | <53 dB(A)                                                                                                                                                                                                  |
| <b>Voltage</b>                 | 100 - 240 V autosensing                                                                                                                                                                                    |
| <b>Power consumption</b>       | 60 Watt printing; <3 W Sleep Mode                                                                                                                                                                          |
| <b>Temperature</b>             | +5° to +40° C; 10% to 85% rel. humidity                                                                                                                                                                    |
| <b>Print volume</b>            | 20.000 pages per month                                                                                                                                                                                     |
| <b>MTBF</b>                    | 25.000 hours @20% duty cycle                                                                                                                                                                               |
| <b>Driver</b>                  | Windows 8/8.1/10/11 and Server 2012/2016/2019/2022; SAP                                                                                                                                                    |

### Configuration:

- **2600+** Standard model

**DASCOM Europe GmbH**  
Hauweg 3 | 89079 Ulm | GERMANY  
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100  
info@dascom.com | www.dascomeurope.de

**DASCOM (Holdings) LTD.**  
R. 1811-1816A | Nan Fung Centre  
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong  
Tel.: +852 2498 1507 | Fax: +852 2413 6047