

DP-530 SE/530L SE

Fast and
ruggedized simplicity



HIGHLIGHTS AT A GLANCE:

- Easy-to-read control panel
- Simple drop-in paper loading
- High-speed signature printing and extensive font and graphic capabilities
- Popular printer emulations provide compatibility
- DP-530 Receipt version / DP-530L Label version
- IP54 per IEC 529

DP-530 SE/530L SE

With the Tally Dascom DP-530 SE series you can concentrate on your job and not on the printer. Although the printer is up to 10% smaller and 40% lighter than comparable models, it makes no compromises. A variety of interfaces and emulations allow the use of DP-530 SE/DP-530L SE in different environments.

Whether water, dust or vibrations, this printer operates reliably. Whether in the basic variant DP-530 SE for receipt documents or in the label version as DP-530L SE. Thanks to different holders, the printer can easily install on mobile dollies or in vehicles.

TECHNICAL SPECIFICATIONS

Print speed	Up to 5 inch/sec (127 mm/sec)
Resolution	203 dpi (8 dots/mm)
Lifetime print head	50 km
Memory	256 MB FLASH, 512 MB DRAM
Print width	Up to 72 mm
Interfaces Standard	USB 2.0
Interfaces Optional	Bluetooth (4.0) or WiFi (802.11 b/g/n)
Bluetooth	Compatible Bluetooth 2.0 Stack Protocols: L2CAP, RFCOMM, SDP Profile: GAP, SDAP, SPP, BTLE
WiFi	Encryption: WEP, WPA-PSK/TKIP, WPA2-AES, 802.1x EAP with TLS, TTLS, LEAP, FAST, PEAP
Administration	Internal Website
Emulations	ESC/POS, ZPL II, CPCL, EPL, PostScript, PDF
Roll diameter	Max. diameter 50,8 mm for DP-530 and 66 mm for DP-530L
Roll capacity	Approx. 28,6 m (equals 188 6" receipts) for DP-530 Approx. 52 m (equals 346 pcs. 6" labels) for DP-530L
Battery	Rechargeable 3 cells Lithium-Ion (3.000 mAh) Endurance more then 3.500 inches per charge/8 hours shift without WiFi Charging time 2 hours
Weight	0,66 kg (incl. battery) for DP-530 0,69 kg (incl. battery) for DP-530L
Dimensions	117 x 155 x 69 mm (W x D x H) for DP-530 117 x 155 x 79 mm (W x D x H) for DP-530L
Voltage	12/24 V
Temperature	-18° to +50° C (printing); -20° bis 60° C (storage)
Humidity	10% to 90% rel. humidity
MTBF	10.000 hours
Drivers	Windows 8/8.1/10 and Server 2012/2016/209; Android; iOS (only WiFi)
Certifications	CE, FCC Class B, UL, E1

Configurations:

• DP-530 SE	Receipt model	• DP-530L SE	Label model
• DP-530 SE BT	Receipt model with Bluetooth	• DP-530L SE BT	Label model with Bluetooth
• DP-530 SE WiFi	Receipt model with WiFi	• DP-530L SE WiFi	Label model with WiFi

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047