



DP-80Full-page mobile printing on the go





HIGHLIGHTS AT A GLANCE:

- Dual serrated tear edges for clean crisp tear off of your documents
- Large function buttons on top cover
- Easy and smooth opening door, with auto loading of paper
- 2ips / 11 ppm print speeds
- Windows, Android, and iOS Bluetooth compatible
- Small foot print design for efficient mounting options



DP-80

The DP-80 series printers are the latest in reliable, compact, and innovative thermal printing. This small, full-page printer is rated at 11ppm, and is capable of using continuous roll, perforated rolls, or single sheet thermal paper.

This printer features USB, Bluetooth or Wi-Fi connectivity, and is compatible with Windows, Android, and iOS Bluetooth operating systems to provide a wide range of connections. The DP-80 is a true drop-in replacement and fits most mounting systems available for in-vehicle printing. Compatible USB cables, and in-vehicle power adaptors make this printer the perfect addition to any public safety vehicle whether you are outfitting a new fleet or updating your current one.

TECHNICAL SPECIFICATIONS

| Print speed | Up to 2 inch/sec (50 mm/sec) |
|---------------------|------------------------------------------------------------|
| Resolution | 203 dp (8 dots/mm) |
| Lifetime print head | 50 km |
| Memory | 256 MB FLASH, 512 MB DRAM |
| Print width | Up to 210 mm |
| Interfaces Standard | USB 2.0 (Typ Mini) |
| Interfaces Optional | Bluetooth (4.0) or WiFi (802.11 b/g/n) |
| Bluetooth | Compatible Bluetooth 4.0 Stack |
| Administration | Internal Website |
| Emulations | ESC/POS, ZPL II, CPCL, PostScript |
| Media | Direct Thermal Roll, Fanfold and Cut Sheet |
| Weight | 0,6 kg |
| Dimensions | 255 x 55 x 30 mm (W x D x H) |
| Voltage | 12-15 V in-vehicle power adapter 100-200 V wall adapter |
| Temperature | -18° to +50° C (printing); -20° bis 60° C (storage) |
| Humidity | 10% to 90% rel. humidity |
| MTBF | 10.000 hours |
| Drivers | Windows 7/8/10/11; Windows Mobile; Android; iOS |
| Certifications | CE, FCC Class B, UL, E1 |
| | |

Configurations:

• DP-80 Standard model • DP-80 BT Bluetooth model • DP-80 WiFi WiFi model



Hart House, Priestley Road Basingstoke | Hampshire RG24 9PU | ENGLAND Tel.: +44 1256 355 130| Fax: +44 1256 481 400 info.gb@dascom.co.uk



Heuweg 3 | 89079 Ulm | GERMANY Tel.: +49 731 2075-0 | Fax: +49 731 2075-100 info@dascom.com | www.dascomeurope.de DASCOM (Holdings) LTD.

R. 1811-1816A | Nan Fung Centre 264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong Tel.: +852 2498 1507 | Fax: +852 2413 6047

