

1120

Compact in size



HIGHLIGHTS AT A GLANCE:

- Compact 18-pin flatbed printer
- Up to 375 characters per second
- Ideal for front and back office applications
- Variety of interfaces
- Small footprint

1120

The Tally Dascom 1120 is a 18 pin serial dot matrix printer with USB interfaces as standard. Compact in size, the 1120 is perfect for industrial environments and front and back office applications where space is limited. With low running costs, high quality output and an easy to use control panel it's ideal for small business, low volume listings and reports, as well as dispatch notes and labels.

In addition to these applications, the 1120 is also well suited to measurement and control systems. Amongst the lowest priced matrix printers available today the 1120 also offers an easy to exchange ribbon. For draft printing it's considerably less expensive running costs make it a viable alternative to low cost ink-jet printers.

TECHNICAL DATA

Print Speed	Fastest Speed: 375 cps Character density 10 / 12 / 15 cpi <i>Draft</i> 250 / 300 / 375 cps <i>NLQ</i> 166 / 200 / 250 cps <i>LQ</i> 83 / 100 / 125 cps
Resolution	up to 144 x 240 dpi
Character Density	10, 12, 15, 17.1, 20 cpi
Line Density	1, 2, 3, 4, 6, 8 lpi
Print head Life	400 million strokes
Memory	up to 256 kB
Standard Connectivity	USB 2.0
Emulation	IBM, Epson ESC P/2
Fonts	Roman, Sans Serif, Courier, Prestige, Script, OCR-B, OCR-A, ORATOR, GOTHIC, SOUVENIR
Consumables	Ribbon: 4 million characters
Paper Handling	Push tractor for fanfold paper and friction for cut sheets
Number of Copies	1 original + 3 copies
Paper Type	Cut sheets, continuous forms, multi-part forms
Paper Size	<i>Cut Sheet</i> Width: 55 to 279 mm Length: min. 55 mm <i>Fanfold paper</i> Width: 42 - 243 mm Length: min 76 mm
Physical Weight	3,3 kg
Physical Size	366 x 314 x 176 mm (L x W x H)
Acoustic	57 dB(A)
Power Voltage	220 - 240 V - 50/60 Hz
Power Consumption	less than 1,9 Watt Sleep Mode
Temperature	+5° to +40° C; 10% to 85% rel. humidity
MTBF	12.000 hours
Driver	Windows 8/ 8.1/10/11
Warranty	For more details please contact your local dealer

Configurations:

- **1120** Standard model with USB interface

DASCOM Europe GmbH
Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.
R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047